

## ARTICLE

### Lifebuoy Light - L161 - including bracket - MED/SOLAS

Number: 3.05.0350

IMPA number: 330330

## SPECIFICATIONS

Measurements: 185 (l) x 106 (w) mm

Weight: 0,30 kg

Made in: United Kingdom

HS Code: 85318070



## DESCRIPTION

The L161 is fully approved to SOLAS/MED standards and also ATEX, IECEx and ETL listing under UL913. It is intrinsically safe (category 1) and as such is suitable for use in hazardous zones 0, 1 and 2. The L161 is our new intrinsically safe Lifebuoy Light and replaces the well-established L40 Light.

### Fit and Forget

All Lifebuoy Lights offer a five year life. No maintenance or replacement batteries are required. This saves time and expense during inspections.

### Compact size

These Lifebuoy Lights are amongst the smallest and lightest lights available on the market today.

### 76 Metres Drop Height

MED/SOLAS and USCG standards call for the Lifebuoy lights to be dropped from 30 metres. All these Lifebuoy lights have passed a drop height test from 76 metres high. This makes these new lifebuoy lights suitable for use on any platform or vessel with high bridge wings.

### Mounting made easy

All Lifebuoy Lights are supplied with a unique mounting bracket, enabling easy fitting in all locations.

### LED Technology

Lifebuoy Lights are using the latest advances in LED technology. They feature very low current consumption and enhanced reliability. All our Lifebuoy Lights feature a flashing light.  
3091

## CERTIFICATIONS



MED



SOLAS



ATEX